

Hazard Register



| | | | |
|----------------------|-------------------|--------------------|---------|
| Type | MULTI TYRE ROLLER | Location | - |
| Make | - | Sale Number | 5049500 |
| Model | - | Lot Number | 36 |
| Serial Number | | | |

| ID | Hazard Type | Hazard Description |
|-----------|---------------------|--|
| 131330.1 | PPE | PERSONAL PROTECTIVE EQUIPMENT (PPE) - IDENTIFY TYPE AND PROVIDE INSTRUCTION/INFORMATION RE: USE, STORAGE, CARE AND MAINTENANCE OF PPE (E.G. EYE & HEAR PROTECTION, DUST MASK ETC.) |
| 131330.2 | Emergency Stop | ENSURE THERE IS AN E-STOP IN CABIN (AS PER MANUFACTURERS SPECIFICATIONS). |
| 131330.3 | Mechanical | STRIKING/CUTTING/CRUSHING - DO NOT PLACE HANDS OR OTHER PARTS OF THE BODY NEAR THE ARTICULTION POINT OF PLANT DURING OPERATION. |
| 131330.4 | Clothing | ENTANGLEMENT - DO NOT OPERATE PLANT WITH LOOSE CLOTHING. |
| 131330.5 | Mechanical | POWER SUPPLY TO THE PLANT MUST BE ISOLATED, DE-ENERGISED BEFORE COMMENCING ANY CLEANING AND OR MAINTENANCE ACTIVITIES. |
| 131330.6 | Thermal Conditions | EXPOSURE TO UV (SUN) RADIATION AND OR HEAT STRESS TO THE OPERATOR. |
| 131330.7 | Rollover | ENSURE A ROLL OVER PROTECTIVE (ROPS) DEVICE IS PRESENT. |
| 131330.8 | High Pressure Fluid | ALL HOSES AND FITTINGS TO BE REGULARLY INSPECTED AND MAINTAINED AS PER THE AUSTRALIAN STANDARD |
| 131330.9 | Plant Operation | ENSURE AN OPERATORS MANUAL IS OBTAINED FOR THIS PLANT. OPERATORS ARE TO FOLLOW THE INSTRUCTIONS IN THE OPERATORS MANUAL. |
| 131330.10 | SLIP TRIP FALL | ENSURE HANDLES AND STEPS IN WORKING ORDER. ENSURE NON SLIP MATERIAL ON STEPS AND IN CABIN IS PRESENT. |
| 131330.11 | Controls | ENSURE DOCUMENTED INSTRUCTIONS PROVIDED FOR THE PLANT. ENSURE THE OPERATOR CONTROLS ARE CLEARLY LABELLED ON THIS PLANT. |
| 131330.12 | Electrical | PLANT NEEDS TO BE REGULARLY INSPECTED AND MAINTAINED AS PER AUSTRALIAN STANDARD: IN-SERVICE SAFETY INSPECTION AND TESTING OF ELECTRICAL EQUIPMENT, AND AUSTRALIAN STANDARD: WIRING RULES. |
| 131330.13 | Registration | ENSURE PLANT APPROPRIATELY REGISTERED FOR ROAD USE. |
| 131330.14 | Ergonomics | ENSURE SEAT BELT AND SEAT ADJUSTOR PRESENT. ENSURE THAT PLANT OPERATORS WEAR SEAT BELT DURING OPERATION. THE SEATS ARE ERGONOMICALLY DESIGNED. THERE ARE SEAT BELTS ON THIS PLANT. |
| 131330.15 | Signage | RISK ASSESS ALL HAZARDS AND APPLY THE APPROPRIATE SAFETY SIGNAGE. ENSURE WARNING LABELS PRESENT FOR ROLLOVER, FAULTY GAUGE CHECK FUEL, DRIVERS RESPONSIBILITIES, PINCH POINTS. ENSURE CRUSH AND READING SAFETY INFORMATION LABELS PRESENT FOR OPERATION PRESENT ON THIS PLANT. |
| 131330.16 | Guarding | ENTANGLEMENT HAZARDS ASSOCIATED WITH EXPOSED MOVING PARTS. THE EXISTING GUARDS NEED TO BE FIXED IN ACCORDANCE WITH AS 4024 SAFE GUARDING OF MACHINERY. |
| 131330.17 | warning device | ENSURE THAT ONE AUDIBLE AND ONE VISUAL WARNING DEVICE ARE WORKING PRIOR TO WORK COMMENCING. ENSURE REVERSE BEEPER IS TESTED PRIOR TO OPERATION IN THE WORKPLACE. |

Hazard Register



| | | |
|-----------|------------|--|
| 131330.18 | Fire | FUELS, HYDRAULIC FLUID EXPLODING. NO NAKED FLAMES OR IGNITION POINTS IN VICINITY WHEN REFUELLING OR MAINTENANCE BEING CONDUCTED. |
| 131330.19 | Noise | SOUND PRESSURE LEVELS NEED TESTING AT OPERATOR STATION. IF SPL GREATER THAN 85 dB(A), CLEAR & VISIBLE WARNINGS MUST BE ATTACHED RE: USE OF HEARING PROTECTION. |
| 131330.20 | Skills | PLANT TO BE USED AND ACCESSED BY COMPETENT/SKILLED PERSONNEL ONLY. |
| 131330.21 | Visibility | ENSURE THAT THERE IS GOOD VISIBILTY WHEN OPERATING THIS PLANT. REVERSE MIRROR IS PRESENT. |

Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

| Likelihood | Consequences |
|--|---|
| <ul style="list-style-type: none">• Frequency and duration of exposure• Probability of occurrence of hazard or event (including part history of incidents)• Possibility to avoid / minimize or limit the damage, impact or harm• Reliability and effectiveness of existing / established systems of control | <ul style="list-style-type: none">• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area• Are temperatures of plant, or chemicals, likely to further injure entrapped person |

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.