

Hazard Register



Type	CONCRETE SAW	Location	Grays Online
Make	-	Sale Number	1967
Model	-	Lot Number	-
Serial Number	-		
	-		

ID	Hazard Type	Hazard Description
143282.1	Plant Structure	PLANT INCL. TOOLS TO BE REGULARLY CHECKED AND CONDITION DOCUMENTED. MAINTAIN RECORDS OF ANY MODIFICATION/CHANGES MADE TO THE PLANT.
143282.2	Signage	ATTACH CLEAR AND VISIBLE HAZARD WARNINGS re HOT SURFACES,SHARP EDGES AND USE OF EYE, FACE PROTECTION.
143282.3	Signage	CONSIDER THE NEED TO ATTACH HAZARD WARNING SIGN RE: HOT SURFACES (DRILL AFTER EXTENDED USE, BITS/TOOLS AND WROKPIECE).
143282.4	Vibration	VIBRATION - ENSURE PLANT IS REGULARLY MAINTAINED ROTATE OPERATORS FREQUENTLY
143282.5	Work Space	FLYING DEBRIS, WET FLOORS, SLIPPERY SURFACES, ISOLATE WORK AREA WITH BARRICADES AND SIGNS AND CLEAN UP FREQUENTLY. PROVIDE PROTECTIVE APRON AND FACESHIELD FOR THE OPERATOR.
143282.6	Guarding	CONCRETE CUTTING BLADE - ENSURE BLADE GUARD IS FITTED BEFORE PLANT IS USED. ATTACH HAZARD WARNING SIGN RE: FRICTION SURFACE AND POTENTIAL SHARP / CUTTING EDGES
143282.7	Manual Handling	HANDLING OF PLANT AND OR WORKPIECES. ENSURE MANUAL HANDLING RISK ASSESSMENT IS CARRIED FOR ALL ACTIVITIES ASSOCIATED WITH THE PLANT E.G. LIFTING OF PLANT, OPERATING POSTURES WHEN HANDLING WORKPIECES ON/OFF THE PLANT.
143282.8	Thermal Conditions	EXPLOSION/FIRE FROM ENGINE, SHUT-OFF ENGINE AND LEAVE TO COOL BEFORE REFUELING
143282.9	Air Quality	EXHAUST EMISSIONS (CARBON MONOXIDE) MAY BE HARMFUL, ENSURE THE PLANT IS OPERATED IN A WELL VENTILATED AREA AND OR EXHAUST FITTED WITH AN EXTRACTION SYSTEM
143282.10	PPE	PERSONAL PROTECTIVE EQUIPMENT (PPE) - IDENTIFY TYPE AND PROVIDE INSTRUCTION/INFORMATION RE: USE, STORAGE, CARE AND MAINTENANCE.
143282.11	Plant Structure	STABILITY OF THE APPLIANCE AND OR ATTACHMENTS TO THE PLANT/APPLIANCE, ENSURE THE PLANT IS PROPERLY RESTRAINED/SUPPORTED.
143282.12	Plant Operation	ALL ENERGY SOURCES ASSOCIATED WITH THE PLANT TO BE ISOLATED WHEN PLANT IS CLEANED/MAINTAINED. ALL (INCL. OPENABLE) GUARDS TO BE REPLACED/FITTED BEFORE THE PLANT IS PUT BACK INTO SERVICE.
143282.13	Air Quality	DUST PARTICLES AND OTHER CHEMICALS ASSOCIATED WITH THE PLANT. DOCUMENT RISK ASSESSMENT, REFER TO MSDS.
143282.14	Signage	ALL OPERATOR CONTROLS AND LEVERS TO BE CLEARLY IDENTIFIED AND LABELLED.
143282.15	Noise	SOUND PRESSURE LEVELS NEED TESTING AT OPERATOR STATION. IF SPL GREATER THAN 85 dB(A), CLEAR & VISIBLE WARNINGS MUST BE ATTACHED re USE OF HEARING PROTECTION.

Hazard Register



143282.16	Plant Operation	NO SERVICE OR MAINTENANCE RECORDS AVAILABLE. PROVIDE/REFER TO ANY MANUFACTURER'S MAINTENENCE, OPERATIONAL AND/OR INSTRUCTION MANUAL.
143282.17	Plant Operation	ATTACH OPERATING INSTRUCTIONS IN A CLEAR AND VISIBLE POSITION TO OPERATOR.
143282.18	Skills	PLANT TO BE USED AND ACCESSED BY COMPETENT/SKILLED PERSONEEL ONLY.

Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
<ul style="list-style-type: none">• Frequency and duration of exposure• Probability of occurrence of hazard or event (including part history of incidents)• Possibility to avoid / minimize or limit the damage, impact or harm• Reliability and effectiveness of existing / established systems of control	<ul style="list-style-type: none">• Assume "worst case" injury, but also competent follow-up medical and rehabilitation support• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area• Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.