

Hazard Register



Type	FUELED COMPRESSOR	Location	
Make	GENERIC	Sale Number	180410
Model	GENERIC.	Lot Number	
Serial Number			

ID	Hazard Type	Hazard Description
68329.1	EMERGENCY STOP.	ENSURE THERE IS AN EMERGENCY STOP BUTTON IS PRESENT ON THIS PLANT. IT IS RECOMMENDED THAT THE EMERGENCY STOP BUTTONS ARE TESTED PRIOR TO USE IN THE WORK PLACE. REGULARLY TEST TO ENSURE THAT IT IS FUNCTIONING CORRECTLY.
68329.2	PROCESS MANUAL.	ENSURE A MANUFACTURER'S OPERATING INSTRUCTIONS IS ATTAINED, DESCRIBING PRE OPERATIONAL CHECKS & PERSONAL PROTECTIVE EQUIPMENT REQUIREMENTS.
68329.3	Plant Operation	OBTAIN, READ, UNDERSTAND AND FOLLOW MANUFACTURER'S INSTRUCTIONS. OBTAIN A COPY OF THE MANUFACTURERS MANUAL.
68329.4	PLANT STRUCTURE.	SEEK TECHNICAL ADVICE FROM THE MANUFACTURER REGARDING SET UP. DO NOT CARRY OUT ANY MODIFICATIONS TO THE PLANT.
68329.5	PLANT OPERATION.	CONDUCT DOCUMENTED PRE-OPERATIONAL CHECKS PRIOR TO EACH USE, REFER TO MANUFACTURER'S OPERATIONAL/MAINTENANCE MANUALS AS APPLICABLE.
68329.7	SKILLS.	MACHINERY TO BE OPERATED BY SKILLED AND COMPETENT OPERATORS ONLY.
68329.8	ELECTRICAL.	ENSURE THAT GROUNDING (EARTHING) OF THE PLANT IS AS PER MANUFACTURER'S RECOMMENDATIONS AND OR AUSTRALIAN STANDARD: WIRING RULES AND INSPECTED AS PER AUSTRALIAN STANDARD: IN-SERVICE SAFETY INSPECTION AND TESTING OF ELECTRICAL EQUIPMENT.
68329.9	PROCESS MANUAL.	ENSURE SERVICE AND MAINTENANCE RECORDS ARE KEPT FOR PLANT OPERATIONS.
68329.10	PLANT STRUCTURE.	PLANT TIP-OVER DURING USE, ALWAYS OPERATE/UNLOAD/LOAD THE PLANT ON FIRM/STABLE GROUND.
68329.11	WORK SPACE.	ENSURE CLEAR AND VISIBLE SIGNAGE ON THE CONTROL PANEL TO ENABLE SAFE USE.
68329.12	NOISE.	SOUND PRESSURE LEVEL NEEDS TESTING AT OPERATOR WORKSTATION. IF GREATER THAN 85dB(A), EXAMINE WAYS TO REDUCE EMISSIONS FROM THE PLANT AND ATTACH CLEAR AND VISIBLE HAZARD WARNING SIGN RE: HEARING PROTECTION.
68329.13	THERMAL CONDITIONS.	EXPLOSION/FIRE FROM ENGINE, SHUT-OFF ENGINE AND LEAVE TO COOL BEFORE REFUELLING, PROVIDE FIRST AID KIT. THERE IS A FIRE EXTINGUISHER ON THIS PLANT. ENSURE THAT THE FIRE EXTINGUISHER IS INSPECTED BY A QUALIFIED EVERY 6 MONTHS.
68329.14	FLAMMABLE SUBSTANCES.	ENSURE THAT FLAMMABLE SUBSTANCES ARE STORED IN A LOCKABLE AND BUNDED STORAGE. ENSURE THAT MATERIAL SAFETY DATA SHEETS ARE OBTAINED. WHEN REFUELLING USE A CLOSED FUNNEL SYSTEM.
68329.15	PPE	PROVIDE INFORMATION/INSTRUCTION ON STORAGE, USE, CARE AND MAINTENANCE OF PERSONAL PROTECTIVE EQUIPMENT.
68329.16	MECHANICAL.	ENTANGLEMENT/STRIKING BY WORKPIECES EJECTING FROM AND OR WITH MOVING PARTS OF THE PLANT, THE DRIVE TO THE PLANT MUST BE STOPPED/DISCONNECTED AND THE MOVING PARTS OF THE PLANT STOPPED BEFORE

Hazard Register

		MAINTENANCE AND OR REMOVING ANY OBSTRUCTIONS NEAR THE PLANT.
68329.17	SIGNAGE.	ATTACH CLEAR & VISIBLE HAZARD SIGNS RE KEEP CLEAR OF MOVING PLANT, HOT SURFACES, OPERATOR WARNINGS, ELECTRICAL WARNINGS. ALL WARNING AND SAFETY INSTRUCTIONAL SIGNS ARE PRESENT AS PER THE MANUFACTURERS SPECIFICATIONS. ALL INSTRUCTIONAL LABELS ARE PRESENT ON THE CONTROL PANEL OF THIS PLANT. THERE IS THE APPROPRIATE SAFETY WARNING AND INSTRUCTIONAL LABELS ON THIS PLANT AS PER THE MANUFACTURERS REQUIREMENTS.
68329.18	CHEMICALS.	CONDUCT DOCUMENTED CHEMICALS RISK ASSESSMENT FOR ALL CHEMICALS USED WITH THE PLANT.
68329.19	AIR QUALITY.	EXHAUST EMISSION (CARBON MONOXIDE) MAY BE HARMFUL, ENSURE THE PLANT IS OPERATED IN A WELL VENTILATED AREA.
68329.20	GUARDING.	ENSURE THAT THE POWERED MOVING OR ROTATING PARTS ARE GUARDED AS PER AUSTRALIAN STANDARD: SAFE GUARDING OF MACHINERY. THE GUARDING IS PRESENT OVER MOVING PARTS OF THIS PLANT.
68329.21	HOT SURFACES.	BURNS.ENSURE THERE IS GUARDING PRESENT OVER THE EXHAUST OF THIS PLANT.
68329.22	PRESSURE TESTING	ENSURE PRESSURE TESTING IS CARRIED OUT AS PER AUSTRALIAN STANDARD, REGULATORS AND LOCAL COUNCIL STANDARDS ARE MET.
68329.23	AIR PRESSURE	ENSURE ALL AIR PRESSURE SAFETY REQUIREMENTS ARE MET REGARDING PPE AND USE

Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Graysonline for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
<ul style="list-style-type: none">• Frequency and duration of exposure• Probability of occurrence of hazard or event (including part history of incidents)• Possibility to avoid / minimize or limit the damage, impact or harm• Reliability and effectiveness of existing / established systems of control	<ul style="list-style-type: none">• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area• Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.