

Hazard Register



Type	LATHE	Location	ENGINEERING AND
Make	SERVIAN	Lot Number	001
Model	3 PHASE	Sale Number	3004382
Serial Number		Vendor	

ID	Hazard Type	Hazard Description
53833.1	Electrical	PLANT TO BE USED WITH AN ELECTRICAL CIRCUIT BREAKER (SAFETY SWITCH) AND OVERLOAD PROTECTION.
53833.2	Striking	WORKPIECES EJECTING FROM THE PLANT. SLIDING GUARD AND PEERING WINDOW HAS DEGRADED IN STRENGTH AND ABILITY TO CONTAIN EJECTED PARTS FROM THE PLANT. REPLACE GUARD OVER SPINDLE. INSTALL INTERLOCK GUARDING IN ACCORDANCE WITH AS4024.1: SAFEGUARDING OF MACHINERY.
53833.3	SLIP TRIP FALL	HOUSEKEEPING PROCEDURES SHOULD BE IMPLEMENTED TO IMPROVE ACCESS OR EGRESS TO OR FROM PLANT. HOSES, CORDS AND OBJECTS IN THE PATH OF OPERATOR.
53833.4	Manual Handling	OPERATOR SPRAINS AND/OR STRAINS FROM MANUAL HANDLING WORK PIECES/PRODUCT ON AND OFF PLANT ITEM OR AS A RESULT OF REPETATIVE BODY MOVEMENT.
53833.5	Cutting, Stabbing and Puncturing	CONTACT AND HANDLING OF SWARF. EMPLOYEES SHOULD ENSURE THE APPROPRIATE PPE IS WORN TO PREVENT CUTTING WITH SWARF.
53833.6	Chemicals	COOLANT, OILS, AND OTHER CHEMICALS USED WITH THE PLANT PROVIDE MSDS AND DOCUMENT CHEMICALS RISK ASSESSMENT FOR THE PLANT.
53833.7	Entanglement	ENTANGLEMENT WITH TURNING CENTRE PLANT ATTACHMENTS WHILE MACHINE OPERATIONAL. GUARDING SHOULD BE IN ACCORDANCE WITH AS4024.1: SAFEGUARDING OF MACHINERY.
53833.8	Noise	SOUND PRESSURE LEVELS NEED TESTING AT OPERATOR STATION. IF SPL GREATER THAN 85 dB(A), CLEAR & VISIBLE WARNINGS MUST BE ATTACHED RE: USE OF HEARING PROTECTION.
53833.9	Guarding	MOVING PARTS OF THE PLANT MAY ENTRAP OR CUT BODY PARTS. ALL FIXED AND OPERABLE GUARDS MUST BE REPLACED AFTER MAINTENANCE/CLEANING ACTIVITIES. ENSURE ANY IN PLACE INTERLOCKING SWITCHES ARE ROUTINELY CHECKED/SERVICED GUARDING SHOULD BE IN ACCORDANCE WITH AS4024.1: SAFEGUARDING OF MACHINERY.
53833.10	Electrical	PLANT NEEDS TO BE REGULARLY INSPECTED AND MAINTAINED AS PER AS/NZS3760: IN-SERVICE SAFETY INSPECTION AND TESTING OF ELECTRICAL EQUIPMENT AND AS/NZS3000: WIRING RULES AND/OR AS1543: ELECTRICAL EQUIPMENT OF INDUSTRIAL MACHINES.
53833.11	Labelling Pipework	ENSURE AIR, OIL AND LUBRICANT LINES ARE APPROPRIATELY IDENTIFIED AND LABELLED AS PER AS1345 : IDENTIFICATION OF THE CONTENTS OF PIPES, CONDUITS AND DUCTS.
53833.12	SAFETY SIGNAGE	OPERATOR INJURY MAY RESULT FROM ILLEGIBLE OR MISSING WARNING LABELS/SIGNAGE (NOISE, PPE, OPERATING INSTRUCTIONS, HOT SURFACES, EXITS, ROTATING FANS, NIP POINTS ECT). REGULAR INSPECTION & REPLACEMENT OF WARNING LABELS (SAFETY DECALS) IS REQUIRED. SIGNAGE IS TO BE COMPLIANT WITH AS 1319 SAFETY SIGNAGE FOR THE OCCUPATIONAL ENVIRONMENT.
53833.13	Operator controls	OPERATOR CONTROLS SHOULD BE LABELLED CLEARLY SO THE OPERATOR IS AWARE OF THE APPROPRIATE CONTROLS.
53833.14	Air Quality	DUST PARTICLES AND OTHER CHEMICALS ASSOCIATED WITH THE PLANT. DOCUMENT RISK ASSESSMENT, REFER TO MSDS.
53833.15	Skills	PLANT TO BE USED AND ACCESSED BY COMPETENT/SKILLED PERSONEL ONLY.
53833.16	PPE	PERSONAL PROTECTIVE EQUIPMENT (PPE) - IDENTIFY TYPE AND PROVIDE INSTRUCTION/INFORMATION RE: USE, STORAGE, CARE AND MAINTENANCE.
53833.17	Instructions	IMPLEMENT SAFE OPERATING PROCEDURES FOR THE OPERATION OF PLANT. ATTACH A COPY OF THE SAFE OPERATING PROCEDURES IN A VISIBLE LOCATION AT OPERATORS WORKSTATION.
53833.18	Maintenance	IMPLEMENT LOCKOUT/TAGOUT SYSTEM FOR MAINTENANCE OPERATIONS CONDUCTED ON THE PLANT

Please refer to asset safety information overleaf

Hazard Register

Occupational Health and Safety

Plant Safety

Purchaser Information

This plant health and safety information has been prepared by Graysonline for the purchaser of the plant item as required by National and State OHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that such hazards have been identified given due consideration to the state of knowledge of the plant item.

If this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to review the hazard register and in consultation with employees, prepare a formal risk assessment for the operation of the plant item in the new environment.

In order to assess the risk, it is necessary to consider the likelihood of an incident that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser to complete the plant assessment.

Likelihood

- Frequency and duration of exposure
- Probability of occurrence of hazard or event (including part history of incidents)
- Possibility to avoid / minimize or limit the damage, impact or harm
- Reliability and effectiveness of existing / established systems of control

Consequences

- Assume “worst case” injury, but also competent follow-up medical and rehabilitation support
- Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured
- Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point
- Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area
- Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all situations, employees/operators must be made aware of the control measures in place to protect them from the plant hazards.