

Hazard Register



Type	POST HOLE DIGGER	Location	
Make	-	Sale Number	1967
Model	-	Lot Number	
Serial Number			

ID	Hazard Type	Hazard Description
143097.1	Guarding	ENSURE THAT TURNING UNIVERSAL JOINTS AND CHAIN DRIVES ARE GUARDED AND THE HOUSING IS CORRECTLY GUARDED TO LIMIT FLYING PROJECTILES AS PER AUSTRALIAN STANDARD: SAFE GUARDING OF MACHINERY.
143097.2	Plant Structure	MACHINERY TIP-OVER DURING LOADING/UNLOADING ON TRANSPORTER. ENSURE THAT NON AUTHORISED PERSONS ARE NOT IN CLOSE PROXIMITY TO LIFTING EQUIPMENT DURING LOADING.
143097.3	Signage	SAFETY SIGNAGE IS NOT PRESENT ON PLANT E G. STRUCK BY, HAND DAMAGE, READ MANUFACTURER'S INSTRUCTIONS AND LIFT POINTS. ENSURE THAT SIGNAGE IS DISPLAYED AS PER THE MANUFACTURERS SPECIFICATION.
143097.4	Controls	NO DOCUMENTED INSTRUCTIONS PROVIDED FOR THE PLANT AND OR OPERATOR CONTROLS NOT CLEARLY LABELLED
143097.5	Mechanical	ENSURE THAT PLANT IS IN CORRECT OPERATIONAL CONDITION AS PER THE MANUFACTURERS SPECIFICATIONS. PLANT SHOULD BE REGULARLY INSPECTED AND MAINTAINED AND RECORDS KEPT.
143097.6	Noise	NOISE. ENSURE THAT NOISE LEVELS BELOW 85dBA WHEN WORKING IN CLOSE PROXIMITY TO PLANT.
143097.7	Work Space	CONTACT WITH MOBILE PLANT
143097.9	Plant Operation	CONTROLS AND MECHANICAL FAILURE OF PLANT AND OR MACHINERY.

Health and Safety
Plant Safety
Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
• Frequency and duration of exposure • Probability of occurrence of hazard or event (including part history of incidents) • Possibility to avoid / minimize or limit the damage, impact or harm • Reliability and effectiveness of existing / established systems of control	• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support • Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured • Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point • Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area • Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

- Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.
Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.
High risk – considered to be unacceptable and requiring action within the short to medium term.
Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.